Listing of Claims:

This listing of claims replaces all prior versions, and listings, of claims in the application:

- (currently amended): An energy dense energetic material comprising:
- a layer of material comprising one or more metals substantially not in oxide form, namely <u>wherein</u> one or more compositions wherein said compositions comprise non-adducted metal hydrides and metals with interstitial hydrogen; and
- a layer of material comprising one or more metals substantially in oxide form; and
- wherein said layers in combination are energetic and have a thickness of less than or equal to approximately 10 nm.
 - 2. (canceled)
- (original): The material of claim 1 comprising a plurality of layers of material comprising one or more metals substantially not in oxide form.
- (original): The material of claim 3 comprising a plurality of layers of material comprising one or more metals substantially in oxide form.
- (original): The material of claim 4 wherein each layer of material comprising one or more metals substantially in oxide form is adjacent to at least one layer of material comprising one or more metals substantially not in oxide form.

2

Patent Application No. 10/759,885

- (original): The material of claim 1 comprising a plurality of layers of material comprising one or more metals substantially in oxide form.
- (original): The material of claim 1 wherein the layer of material comprising one or more metals substantially not in oxide form comprises one or more metals selected from the group consisting of AI, Ti, Li, and Mg.
- (original): The material of claim 1 wherein the layer of material comprising one or more metals substantially in oxide form comprises one or more metals selected from the group consisting of W, P, Fe, and Mn.

9. (canceled)

- 10. (previously presented): The material of claim 1 wherein the layer of material comprising one or more metals substantially not in oxide form comprises one or more non-adducted metal hydrides.
- 11. (previously presented): The material of claim 1 wherein the layer of material comprising one or more metals substantially not in oxide form comprises one or more metals with interstitial hydrogen.
- (original): The material of claim 1 fabricated by plasma enhanced chemical vapor deposition.
- 13. (original): The material of claim 1 adhered to a substrate selected from the group consisting of polymers, ceramics, glass, metals, and curved surfaces.

3

- (previously presented): The material of claim 1 wherein said layers form an
 energetic material selected from the group consisting of TNT, RDX, Tritonal, and AFX-757.
- (original): The material of claim 1 wherein said material forms energetic fragments upon detonation.
- 16. (original): The material of claim 15 wherein said energetic fragments comprise a material selected from the group consisting of elemental Mn and elemental P.
- (original): The material of claim 1 wherein said material is useful in an anti-tamper device.
 - 18. (previously presented): An energy dense energetic material comprising:
- a first layer of material, comprising one or more compositions selected from the group consisting of non-adducted metal hydrides and metals with interstitial hydrogen; and
- a second layer of material, comprising one or more metals substantially in oxide form; and
- wherein said layers in combination are energetic and have a thickness of less than or equal to approximately 10 nm.
- 19. (previously presented): The material of claim 18 wherein said first layer of material comprises one or more non-adducted metal hydrides.

- (original): The material of claim 18 wherein said first layer of material comprises one
 or more metals with interstitial hydrogen.
- 21. (previously presented): A method of making an energy dense energetic material, the method comprising the steps of:
- depositing a layer of material comprising one or more metals substantially not in oxide form, namely one or more compositions selected from the group consisting of non-adducted metal hydrides and metals with interstitial hydrogen; and
- depositing an adjacent layer of material comprising one or more metals substantially in oxide form; and
- wherein said layers in combination are energetic and have a thickness of less than or equal to approximately 10 nm.